



SNA Terminal Blocks
T&B Catalog Number:

010500220

UPC Number:

66201995345

Status:

Active

Description:

Orange, feed through terminal block with 6 mm spacing, 30 Amp rated UL current with screw clamp connection that accepts 22-10 AWG UL wire range

Features

	Self-locking clamp design prevents screw loosening
	Funneled side entry for up to two ferruled or non-ferruled solid or stranded wires
	Touch-safe IP20 protection
	High quality steel offers a very high over-torque resistance
	Compensates for the flattening of copper under contact pressure
	Clamp is protected from harsh environments by a zinc bichromate surface treatment

Application

For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.

General

Style	Feed Through
Color	Orange
Mounting	DIN 1-3
Series	M 4/6
Connection Technology	Screw Clamp
UL Wire Range (AWG)	22-10
Rated IEC Wire Range (Solid) (mm ²)	4
Rated CSA Wire Size (AWG)	10

Dimension Information

L x W x H (mm)	44.5 x 6 x 53
Spacing (mm)	6
L x W x H (in)	1.75 x 0.238 x 2.18
Spacing (inches)	0.236

Specifications

UL Current (Amps)	30
UL Voltage (VAC)	600
Rated UL Wire Size (AWG)	10
IEC Voltage (VAC)	800
IEC Current (Amps)	32
CSA Voltage (VAC)	600
CSA Current (Amps)	25

Packaging

T&B Order Multiple	50
T&B Inner Pack	50
Package in Units	2000
T&B Sold in UOM	Each
T&B Weight Per UOM	1.94 lbs. per 100

Certifications

Approvals	UL, IEC, CSA
-----------	--------------

For further technical assistance, please contact us...

ABB, Inc.
Low Voltage Products
16250 W. Glendale Drive
New Berlin, WI 53151
Phone: 888-385-1211
Fax: 800-726-1411

USA Technical Support & Customer Service
888-385-1211, Option 4
7:30AM to 5:30PM, CST
Monday - Friday
Email: lvps.support@us.abb.com